

Параметры для закупки серверов (с шкафом и ИБП) и коммутационного оборудования

№	Наименование	Кол-во
1.	Сервер в комплекте: – Intel Xeon Gold 6258R, 2.7G, 28C/48T, 10.4GT/s, 38.5 M Cache, Turbo, HT (205W) DDR4-2933 – 2 штуки; – Chassis with Up to 24 x 2.5" Hard Drives for 2CPU – 1 штука; – PowerEdge 2U LCD Bezel – 1 штука; – Quick Sync 2 (At-the-box mgmt) – 1 штука; – 64GB RDIMM, 3200MT/s, Dual Rank – 8 штуки; – 3.84TB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD, – 10 штук; – 800GB SSD SAS Write Intensive 12Gbps 512e 2.5in Hot Plug Drive, PM5-M, 10 DWPD, – 6 штуки; – BOSS controller card + with 2 M.2 Sticks 480GB (RAID 1), FH – 1 штука; – HBA330 Controller Adapter, Low Profile – 1 штука; – Dual, Hot-plug, Redundant Power Supply (1+1), 1600W, 250 Volt Power Cord Required for Use – 1 штука; – C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord – 2 штуки; – Broadcom 5720 Quad Port 1GbE BASE-T, rNDC – 1 штука; – Mellanox ConnectX-5 Dual Port 10/25GbE SFP28 Adapter, PCIe Full Height – 2 штуки; – Broadcom 5719 Quad Port 1GbE BASE-T Adapter, PCIe Full Height – 1 штука; – OpenManage Integration for VMware vCenter - 1 host increment, 3-year license - Digitally Fulfilled – 1 штука; – OpenManage Enterprise Advanced – 1 штука; – iDRAC9 Datacenter 14G – 1 штука.	3
2.	Коммутатор 24x 25GbE SFP28, 4x 100GbE QSFP28 ports, PSU to IO air, 2x PSU, OS10 в комплекте: – Jumper Cord - C13/C14, 2M, 250V, 10A (EU, TW, APCC countries except ANZ) – 2 штуки; – Networking Cable 100GbE, QSFP28 to QSFP28, Passive Copper Direct Attach Cable, 1 Meter – 1 штука; – Networking Cable, 100GbE QSFP28 to QSFP28, Passive Copper Direct Attach Cable, 0.5 Meter – 1 штука; – Networking, Cable, SFP28 to SFP28, 25GbE, Passive Copper Twinax Direct Attach Cable, 3 Meter – 10 штук; – OS10 Enterprise, S5224F-ON – 1 штука.	2
3.	Коммутатор 48x 1GbE, 4x SFP+ 10GbE ports, Stacking, PSU to IO air, 1x AC PSU, DNOS 9 в комплекте: – Rack Power Cord 2M, C13/C14, 12A – 2 штуки; – Power Supply, 200w, PSU to IO airflow, S3048-ON – 1 штука; – OS9 installed on S3048-ON, with entitlement to OS10 Enterprise – 1 штука.	2
4.	Коммутатор L3, 24x 1GbE, 2xCombo, 2x 10GbE SFP+ fixed ports, Stacking, IO to PSU airflow, 1x AC PSU в комплекте: – Rack Power Cord 2M, C13/C14, 12A – 2 штуки; – Power Supply, 200w, S3124/S3148, with V-Lock, adds redundancy to non-POE S3100 series switches – 1 штука.	1
5.	Серверный шкаф Dell 42U Rack Enclosure в составе: – Rack PDU Basic (APC PN: AP7553) Zero U, 32A 230V 20xC13 & 4xC19 Outlets, Built-in IEC309 32A Pow Cord – 2 штуки; – 1U 19" Black Modular Toolless Airflow Management Blanking Panel - Qty 10 – 1 штука; – Vertical Cable Organizer, 8 Cable Rings, Zero U – 1 штука; – Power Cord, C19 to CEE/7 Schuko, 2.5m – 2 штуки; – Power Cord, C19 to IEC309 16A, 2.5m – 2 штуки.	1
6.	Источник бесперебойного питания Dell Smart-UPS SRT 8000VA RM 6U 230V On Line, 3Yr Warranty Inc Battery, NMC is included	2